RAL920000121US1
C. Basso, et al
Data Structures for Efficient Processing
of IP Fragmentation and Reassembly
1/7

FIG. 1

RAL920000121US1
C Basso, et al
Data Structures for Efficient Processing
of IP Fragmentation and Reassembly
2/7

FIG. 2

RAL920000121US1
C Basso, et al
Data Structures for Efficient Processing
of IP Fragmentation and Reassembly
3/7

FIG. 3

RAL920000121US1
C Basso, et al
Data Structures for Efficient Processing
of IP Fragmentation and Reassembly
4/7

FIG. 4

Word	Bits																															
	3 1	3 0	2 9	2 8	2 7	2 6	2 5	2 4	2 3	2 2	2 1	2 0	1 9	1 8	1 7	1 6	1 5	1 4	1 3	1 2	1 1	1 0	9	8	7	6	5	4	3	2	1	0
0	Message ID								Message Parameters																							
1	Data																															
...	...																															
N-1	Data																															

RAL920000121US1
C Basso, et al
Data Structures for Efficient Processing
of IP Fragmentation and Reassembly
5/7

FIG. 5

FIG. 6

601 EPC issues credit for Dataflow to dispatch frames to EPC

602 Frame Dispatched?

603 Wait ← No

604 EPC requests Lease of "N" free FCB addresses from Dataflow

605 FCB Addresses transferred?

606 Wait ← No

607 EPC requests Lease of "N" buffers from Dataflow

608 Buffers Leased?

609 Wait ← No

610 Follow original frame buffer chain to find segmentation points

611 Write new IP headers to header buffers

612 Chain in new header buffers at proper points

613 Enqueue as a multicast frame

FIG. 7

EPC issues credits
for Dataflow to
dispatch frames to
EPC — *701*

Frames
Dispatched? — *702*

No → Wait — *703*

Yes

Follow the chain of first
N-1 fragments to locate
buffer chaining points — *704*

Chain "tail" of one
fragment to "head"
of next fragment — *705*

Enqueue
reassembled
frame using FCBA
of first fragment — *706*

EPC returns
remaining FCBAs to
Dataflow — *707*

FCBAs
returned? — *708*

No → Wait — *709*

Yes

Done — *710*